

- 1/1 - (C) WPI / DERWENT
- AN - 89-201887 ç25!
- AP - JP870298642 871125
- PR - JP870298642 871125
- TI - Easily-adhered decorative wall-covering sheet -
comprises pressure sensitive adhering waterproof rubber
sheet layer, substrate sheet layer, top coat etc.
- IW - EASY ADHERE DECORATE WALL COVER SHEET COMPRISE PRESSURE
SENSITIVE ADHERE WATERPROOF RUBBER SHEET LAYER
SUBSTRATE SHEET LAYER TOP COAT
- PA - (FUJI-N) FUJIWARA KAGAKU KK
- PN - JP1139252 A 890531 DW8928 007pp
- ORD - 1989-05-31
- IC - B32B25/08 ; D06N7/04 ; E04F13/00
- FS - CPI;GMPI
- DC - A84 G03 P73 Q45
- AB - J01139252 An easily-adhering decorative wall-covering
sheet comprises a pressure-sensitive adhering
waterproof rubber sheet layer, a substrate sheet layer,
a waterproof coatings layer, and a top coat layer,
laminated in this order from wall to face.
- The pressure-sensitive waterproof rubber sheet layer is
of e.g. non-crosslinked rubber e.g. natural rubber,
butyl rubber, polybutadiene rubber, blend of rubber and
asphalt. The substrate sheet is (A) paper, woven or
unwoven fabric, into which the waterproof coatings
penetrates, and which is made of e.g. inorganic fibre
(of e.g. ceramics, glass), organic fibre (of e.g.
polyester, acrylic resin, vinylon, PVC), or (B)
reinforcing sheet, into which the waterproof coatings
does not penetrate, e.g. polyester film, fibrous fabric
coated with resinous coatings, laminate of said fibrous
fabric and resinous film or metallic foil, etc.
- USE/ADVANTAGE - The wall-covering sheet can be adhered
easily onto e.g. internal wall of bath room, partition
wall or metal furniture of e.g. (galvanized or
coloured) steel sheet, aluminium sheet, external wall
of e.g. ALC sheet, PC sheet, pulp cement sheet, to
provide decoration, waterproof properties, mildew
proofing properties, etc.